

C-TECH RUBBER PIPE PRODUCTS

PIPE JOINT LUBRICANT

MATERIAL SAFETY DATA SHEET:

Product Name: PL1 Pipe Lubricant
Data Issued: July 2007

Specification:

Usage: Water soluble pipe lubricant for joining pipes with rubber gaskets.



Description:

- Usage: Water soluble pipe lubricant for joining pipe and fittings with rubber, synthetic rubber or plastic gaskets. NON-TOXIC. For use on PW DWF and sewer systems. Adheres to wet and dry surfaces.
- Useable from - 10°C to 80°C.
- Does not support bacterial growth.
- Contains a biocide free of AOX and VOC.
- Contains no petroleum based substances.
- Contains no known carcinogens.

Properties:

SG: 0.970	PH: 7.6 to 8.1
Flash point: Nil	Viscosity: Gel
Flammability: Nil	Boiling Point: 109°C
Solubility in water: Complete	Appearance: Off white paste.
Odour: Mild	Reactivity: Nil

Health Hazard Information:

Acute effects

Swallowed: Non toxic, may irritate stomach.

Eye: Will irritate eyes.

Inhaled: Nil

Safety:

- ☑ In case of contact with eyes, flush with water for 15 minutes.
- Rinse off skin with water.
- If irritation persists, consult physician.
- If swallowed give water and milk. Do not induce vomiting.
- Not an irritant if inhaled.
- Toxicity low.
- Advice to doctor, treat symptomatically.

*Used for
lubricating
rubber pipe
joints to assist
fitting.*

☑ **Safe Handling:**

Transport: No special requirements.

Handling: Use gloves when applying to gaskets.

Storage: No special requirements.

Spills: Clean up with scoop or rags and wash with water.

Disposal: Dispose to local authorities requirements.

Fire Hazard: Nil

Explosion Hazard: Nil

Other Information

Contact:

Laboratory on (02) 9829 3022

C-TECH RUBBER P/L
ABN - 85 - 003 704 612
17 Devon Road
Ingleburn NSW 2565
Australia

C-Tech Rubber USA LLC
Ph: 843 856 8384
Fax: 843 216 7985
Cell: 843 822 0664

In Australia:

PHONE: 61-2-9829 3022

FAX: 61-2-9829 4085

USA

PHONE: 1 843 856 8384